

McGINN & GIBB, PLLC
A PROFESSIONAL LIMITED LIABILITY COMPANY
PATENTS, TRADEMARKS, COPYRIGHTS, AND INTELLECTUAL PROPERTY LAW
8321 OLD COURTHOUSE RD, SUITE 200
VIENNA, VIRGINIA 22182-3817
TELEPHONE (703) 761-4100
FACSIMILE (703) 761-2375

**APPLICATION
FOR
UNITED STATES
LETTERS PATENT**

APPLICANT: Nagaki et al.

FOR: DISK DRIVE DEVICE

DOCKET NO.: PU01-0167

09839538-042301
106240-05565860

DECEMBER IN DECEMBER

1. Field of the Invention

2. Description of Related Art

Car navigation systems mainly use DVDs as the storage, while the use of HDD is expected in the future.

The basic construction of an HDD is shown in Fig. 1. The shown HDD is a ramped loading type device in which a magnetic head 51 provided at a tip end of an actuator 54 is mechanically raised from the magnetic disk surface to float.

1

for driving the magnetic head 51 are significantly lowered.

A power supply is necessary to carry out this emergency unloading function. Meanwhile, according to one known technique, counter electromotive force, in other words, no-loaded electromotive force generated by the inertial rotation of the spindle motor 52 is used to perform the operation when the power supplies are both down as described above.

When this technique is applied to a disk drive device mounted in an engine driven vehicle, as the battery voltage significantly drops at the start of the engine, the above emergency unloading operation is performed each time the engine is started.

Fig. 3 shows an example of a power supply circuit in an engine driven vehicle. More specifically, an alternator G is driven by an engine which is not shown. An alternate power supplied from the alternator G is rectified and smoothed by a rectifier D and supplied to a battery B. The battery voltage V_b of the battery B is supplied to a movable terminal m of an engine key switch SW. The engine key switch SW has fixed terminals ACC, ON and ST, and the battery voltage V_b passed through the terminal ACC is supplied to a light load such as audio equipment as an ACC power supply. The battery voltage V_b passed through the terminal ON is supplied to a heavy load HL such as a power window as an ON power supply. The battery voltage V_b passed through the terminal ST is supplied to a starting

[illegible][illegible][illegible][illegible][illegible]

for detecting an engine start of the vehicle, and the disk drive device is driven after an engine start of the vehicle is detected.

Thus, emergency unloading at the start of the engine can be prevented, and the reduction in emergency unloading occurrence reduces the number of collisions between the head and the ramp. As a result, the head may have a prolonged life and the disk drive device can achieve improved reliability as an HDD.

A disk drive device according to a second aspect of the present invention includes an information recording disk and is driven by a vehicle power supply voltage. The disk drive device includes a head for reading/writing information from/to the information disk, a head driving part for giving a driving instruction to the head, an engine start detecting part for detecting an engine start of the vehicle, and a head movement allowing part for allowing the head to be moved by the head driving part after an engine start of the vehicle is detected by the engine start detecting part.

Thus, the HDD becomes accessible after the engine is activated, and therefore emergency unloading occurrence at the start of the engine can be prevented. The reduction in emergency unloading occurrence reduces the number of collisions between the head and the ramp, so that the head may have a prolonged life and the disk drive may achieve improved reliability as an HDD.

A disk drive device according to a third aspect of the present invention further includes in the disk drive device according to the first or second aspect of the invention, a forcible moving part for forcibly moving the head to a retreat position when the power supply voltage in the vehicle is interrupted.

A disk drive device according to a fourth aspect of the present invention is based on the third aspect of the invention, and the forcible moving part forcibly moves the head to the retreat position by providing the head driving part with counter electromotive force generated by the inertial rotation of a spindle motor driving the recording medium to rotate. Thus, the head can surely be returned to the retreat position if the power supply is interrupted, so that the HDD including the head can be prevented from being critically damaged.

A disk drive device according to a fifth aspect of the present invention further includes in the disk drive device according to the first to fourth aspects of the invention, a voltage value monitoring circuit for monitoring voltage values on a first power supply line provided with a backup power supply and a second power supply line provided with a power supply when an engine key is inserted and turned from a first position to a second position. The engine start detecting part outputs an engine start detection signal when the voltage value on the second power supply line reaches a prescribed value, and then the value on the first

detecting part outputs a signal validated when the activation of a starter-motor is sensed.

Thus, the engine start can be detected based on the outputs of various sensors or by detecting the traveling of the vehicle, and emergency unloading at the start of the engine can be prevented by activating the HDD or allowing the head to move after the detection. As a result, emergency unloading at the start of the engine can be prevented, and the reduction in the emergency unloading occurrence reduces the number of collisions between the head and the ramp. Therefore, the head may have a prolonged life and the disk drive device may achieve improved reliability as an HDD.

A disk drive device according to a fifteenth aspect of the present invention is based on any one of the tenth to fourteenth aspects of the invention, and map information in the previous off state of the engine is backed up in a memory. The information is displayed on a screen in response to detection of a power supply being provided to the second power supply line. Thus, a map is displayed as the driver waits for the HDD to be driven, and therefore the driver may be relieved from vexation during the waiting.

In order to achieve the above described objects, a disk drive device according to a sixteenth aspect of the present invention is driven by a vehicle power supply voltage in a vehicle. The disk drive device includes a counter for starting counting operation based on a

prescribed signal related to a key switch in the vehicle and a controller for driving the disk drive device when the counter has counted a first prescribed time period.

A disk drive device according to a seventeenth aspect of the present invention is driven by a power supply voltage in a vehicle. The disk drive device further includes a head for reading/writing information from/to a recording medium mounted to the disk drive device, a head driving part for giving a driving instruction to the head, a counter for starting counting operation based on a prescribed signal related to a key switch in the vehicle and a head movement allowing part allowing the head to be moved by the head driving part when the counter has counted a first prescribed time period.

A disk drive device according to an eighteenth aspect of the present invention is based on the sixteenth or seventeenth aspect of the present invention. The disk drive device further includes a power supply part for providing a power supply voltage to each part of the disk drive device in connection with the key switch in the vehicle. The counter starts counting operation after the power supply voltage by the power supply part is supplied to the disk drive device by the key switch.

A disk drive device according to a nineteenth aspect of the present invention is based on the sixteenth to eighteenth aspects of the present invention. The disk drive device further includes a voltage monitoring circuit

for monitoring a voltage value at the power supply part. The controller detects a voltage value result at the voltage monitoring circuit after the first prescribed time period, controls the counter to count again when the voltage value is lower than a prescribed value, and controls the disk drive device to be driven when the counter has counted a second prescribed time period.

A disk drive device according to a twentieth aspect of the present invention is based on any one of the sixteenth to nineteenth aspects of the present invention. The disk drive device further includes forcible moving part forcibly moving the head to a retreat position when the power supply voltage at the vehicle is interrupted.

A disk drive device according to a twenty-first aspect of the present invention is based on any one of the sixteenth to twentieth aspects of the present invention. The forcible moving part forcibly moves the head to a retreat position by providing the head driving part with counter electromotive force generated by the inertial rotation of a spindle motor driving the recording medium to rotate.

A disk drive device according to a twenty-second aspect of the present invention is based on any one of the sixteenth to twenty-first aspect of the present invention.

The disk drive device further includes an engine start detecting part for detecting a start of an engine in the vehicle. The controller controls the disk drive device to

be driven when an engine start of the vehicle is detected by the engine start detecting part during the operation of the counter counting said first prescribed time period.

By the above-described constructions, for a vehicle without a voltage drop at the start of the engine, the engine start can be detected by monitoring using a timer. Meanwhile, for a vehicle with a voltage drop, a disk drive device can be started in an earlier timing. The head is allowed to move after the detection time point, so that emergency unloading at the start of the engine may be minimum, or avoided. Therefore, emergency unloading occurrence may be reduced, which reduces the number of collisions between the head and the ramp, so that the head may have a prolonged life and the disk drive device may have improved reliability as an HDD for vehicle.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a plan view of the basic structure of a ramped loading type HDD;

Fig. 2 is a sectional view for use in illustration of the positional relation between the ramp and the head in Fig. 1;

Fig. 3 is a block diagram of a power supply system in an engine driven vehicle;

Figs. 4A and 4B are timing charts for use in illustration of changes in power supply voltages at the start of the engine;

Fig. 5 is a block diagram of a car navigation system

including an HDD according to the present invention;

Fig. 6 is a block diagram of the HDD in the system of Fig. 5;

Figs. 7A and 7B are timing charts for use in illustration of an example of the operation of an engine start detecting device in the HDD in Fig. 6;

Fig. 8 is a block diagram showing an embodiment including a circuit for monitoring a voltage on each power supply line connected to a key switch added to the embodiment shown in Fig. 6;

Figs. 9A to 9D are timing charts for illustrating the operation of the engine start detecting device shown in Fig. 8;

Fig. 10 is a schematic view of a specific example of various sensors shown in Fig. 8;

Fig. 11 is a timing chart for use in illustration of the relation between the generation state of a vehicle speed pulse and the activation of an HDD;

Fig. 12 is a block diagram showing an HDD in the system as shown in Fig. 5 according to another embodiment of the invention;

Figs. 13A and 13B are timing charts for illustrating the timing of activating an HDD using a timer;

Figs. 14A and 14B are timing charts for illustrating the timing of activating an HDD using a timer according to another embodiment of the invention;

Figs. 15A and 15B are timing charts for illustrating

the timing of activating an HDD using a timer according to yet another embodiment;

Figs. 16A and 16B are timing charts for illustrating the timing of activating an HDD using a timer according to a still further embodiment;

Fig. 17 is a block diagram of the embodiment as shown in Fig. 12 with an additional circuit for monitoring each power supply line connected to an IG switch; and

Figs. 18A to 18D are timing charts for illustrating the operation of an engine start detecting device according to the embodiment shown in Fig. 17.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 5 is a block diagram showing the configuration of a car navigation system provided with a disk drive device according to the present invention. Herein, an HDD is used rather than a DVD as a map information storing part for a car navigation system by way of illustration. Note that while the present invention is not limited to the car navigation system, but also applicable to anything provided with an HDD in audio equipment for vehicle, the car navigation will be described as one embodiment. The disk drive device according to the present invention includes a host CPU 11 as a main feature of control, a ROM 12, a RAM 13, a timer LSI 14, a hard disk drive (HDD) 15, a sensor 16, a GPS receiver 17, an interface 18, an input device 19, a display 20, a display controller 21, a display memory 22, a voice sound processing circuit 23, a speaker 24, a power

supply circuit for vehicle 25, a hard disk controller HDC 26, and a backup RAM 27.

The host CPU 11 achieves general control of navigation such as searching the location of a destination and directing a route based on programs stored in the ROM 12 and the RAM 13, and also controls units 12, 13, 14, 27, 19, 23, 18, 26 and 21 connected to a system bus 10. A timer LSI 14 has its time count value set in a programmable manner by the host CPU 11, and issues an interrupt at time up to let the interrupt processing routine to take over the processing. Here, the driving timing of the HDD after the start of the engine is specified.

53/61
The HDD 15 is provided with a measure to prevent emergency unloading according to the present invention, and is disconnected with the system bus 10 through the HDC 26. The HDC 26 carries out format control of a magnetic disk mounted to the HDD 15, and also serves as a host interface and an HDD interface. The sensor 16 includes a group of sensors required by a car navigation system for autonomous traveling, and for example includes a vehicle speed sensor and a gyro sensor. The sensor 16 is connected with the system bus 10 through the interface 18. The interface 18 is supplied with the output of the GPS receiver 17, and hybrid traveling control based on the GPS-measured position and autonomous traveling is carried out.

The display 20 includes a liquid crystal display monitor and a processing content such as map information

written by the host CPU 11 in the display memory 22 is read by a display controller 21 for display. According to the present invention, during the period between the supply of ACC power supply and the activation of the HDD or for a while after the activation, map information representing the position of the vehicle itself at the previous engine termination which has been written in the backup RAM 27 is displayed.

The input device 19 is a remote control device or console used as a GUI for inputting commands or communication between the navigation system and the display 20. The voice sound processing circuit 23 serves as a GUI by emitting a voice sound guide or receiving an input voice sound for communication with the navigation system. The voice sound guide is output through the speaker 24. A power supply circuit 25 for vehicle includes a backup power supply line (constant power supply line) and an ACC power supply line as described above.

Fig. 6 is a diagram showing in detail the configuration of the HDD 15 and the power supply circuit 25 in Fig. 5 and an engine start detecting device 30 for detecting the start of the engine. As shown, the power supply circuit 25 for vehicle includes two power supply lines, a backup power supply line 251 and an ACC power supply line 252.

The HDD 15 includes an internal CPU 152 as a main feature, a host interface circuit 151, a program memory 153,

a data memory 154, an HDD interface circuit 155, an R/W (reading/writing) circuit 156, a head driving control circuit 157, a spindle motor control circuit 158, a magnetic head 51, a voice coil motor (VCM) 160, and a spindle motor 161.

The above described host interface circuit 151, the internal CPU 152, the program memory 153, the data memory 154, and the HDD interface circuit 155 are connected in common to the HDD system bus 150.

The internal CPU 152 receives a command (such as Seek, Read/Write) from the host CPU 11 in Fig. 5 through the host interface 151, and carries out the command control through the HDD interface circuit 155 according to a program stored in the program memory 153. Data read/written from/to a magnetic disk through the magnetic head is controlled by the R/W circuit 156, while the VCM motor 160 is driven under the control of the head driving control circuit 157.

The spindle motor 161 is driven under the control of the spindle motor control circuit 158. Note that counter electromotive force generated by the inertial rotation of the spindle motor when the power supply is off is supplied from the spindle motor 161 to the head driving control circuit 157 through a line 170.

The engine start detecting device 30 includes a voltage value monitoring circuit 301, a threshold setting circuit 302, an engine start detecting circuit 303, and a group of sensors 304. The voltage value monitoring circuit

09035538-042301

301 monitors the voltage values on the backup power supply line 251 and ACC power supply line 252 supplied from the two power supplies described above, and notifies the engine start detecting circuit 303 of the values. A threshold value to detect a momentary shutoff is set at the threshold setting circuit 304, and the engine start detecting circuit 303 is notified of the value. The engine start detecting circuit 303 obtains voltage value data from the voltage value monitoring circuit 301 and the threshold setting circuit 302 and then supplies an activation signal to the HDD in response to a detected engine start timing according to the process as will be described.

The engine start detecting circuit 303 is connected with the group of sensors 304 as an option. In this case, a signal to trigger detection of the engine start timing must be received and internal program-wise determination is necessary without the voltage value monitoring operation as described above. Therefore, program logics by microcomputers or the like are used for monitoring and control. In this case, as the group of sensors 304, a tachometer, a vibration sensor, a starter-motor, a generator and the like would thus be necessary in addition to the sensor 16 provided as part of the car navigation system. These will be detailed.

The activation timing of the HDD according to the present invention will be now described. According to the embodiment, the start of the engine is detected, so that

after a momentary shutoff, the activation of the HDD is controlled and emergency unloading at the start of the engine is prevented. As the part for detecting the start of the engine, the case of monitoring the voltage values on the backup power supply line 251 and the ACC power supply line 252 will be described by way of illustration.

Figs. 7A and 7B are timing charts for use in illustration of the timing of detecting the start of the engine using the engine start detecting device 30. Fig. 7A shows the voltage waveform at the backup power supply line 251, while Fig. 7B shows the voltage waveform at the ACC power supply line 252. A threshold value SL is a prescribed voltage value, 9V for example according to the embodiment. This value is set so that the voltage value at a momentary shutoff caused at the vehicle is lower than SL.

05839533-042301
22

The driver inserts the engine key in the LOCK position to release the lock, and turns the key to the ACC position (I). Thus, the ACC power supply rises for example to 12V, and the key is then turned to the ST position (III) through the ON position (II), which starts the starter-motor and voltage rises both on the backup power supply line 251 and the ACC power supply line 252. After a prescribed time period, the engine starts (IV), and the ACC power supply line 252 and the backup power supply line 251 rise again to the original voltage value 12V, and a steady state is regained. Note that the time period between the ACC position, the start of the starter-motor and the start of

05839538-042301

the engine is random. Here, in order to make sure that the emergency unloading is avoided, the engine start position (the position IV) needs only be detected, and then an activation instruction may be given to the HDD. Therefore, the engine start detecting circuit 303 monitors if the voltage value on the ACC power supply line 252 exceeds the level of a prescribed threshold value SL through the voltage value monitoring circuit 301. If it exceeds the threshold value SL, the engine key has come to the position of ACC, and it is then monitored whether or not the engine is provided with a power supply. More specifically, the engine start detecting circuit 303 monitors the voltage value on the backup power supply line 251 through the voltage value monitoring circuit 301. It is monitored whether or not the voltage value on the backup power supply line 251 is lower than the prescribed threshold value SL. Here, it may be possible to monitor whether or not the two power supply lines, the backup power supply line 251 and the ACC power supply line 252 are both below the prescribed threshold value SL, while monitoring only the ACC power supply line 252 does not allow the start of the engine to be surely detected. This is because the engine key may be returned to the position of the key LOCK from the ACC position. Therefore, after the backup power supply line 251 becomes higher than the prescribed threshold value SL, the backup power supply line 251 or the two power supply lines, the backup power supply line 251 and the ACC power

supply line 252 must be monitored.

When the voltage value on the power supply line is lower than the prescribed threshold value SL, the engine key has come to the ST position (III) through the ACC position (I) and the ON position (II), it is monitored whether the engine starts or not. More specifically, the engine start detecting circuit 303 monitors whether the voltage value on the backup power supply line 251 exceeds the prescribed threshold value SL through the voltage value monitoring circuit 301. If it exceeds the prescribed threshold value SL, the engine has started, and therefore an instruction signal corresponding to the start of the engine is supplied to the HDD 15. Note that in the detection of the start of the engine, it can be monitored whether or not the two power supply lines, the backup power supply line 251 and the ACC power supply line 252 are higher than the prescribed threshold value SL.

The HDD 15 receives the instruction signal at the internal CPU 152, and the magnetic head 51 is allowed to move in response to an instruction from the internal CPU 152. As described above, according to the embodiment, voltage values of the two power supply lines, the backup line 251 and the ACC power supply line 252 may be monitored to surely detect the start of the engine, and then the magnetic head 51 of the HDD 15 is allowed to move.

Therefore, the emergency unloading by the momentary shutoff caused at the start of the engine can be avoided,

and the collision between the magnetic head 51 and the ramp 55 at the start of the engine can be prevented. Note that in the above described embodiment, the magnetic head 51 is allowed to move after the start of the engine, while the power supply for the HDD may be kept off before the start of the engine, and the HDD may be turned on after the start of the engine is detected by the above described part. A method of detecting the start of the engine using power supply lines connected to the key switch will be now described.

Fig. 8 is a diagram of the configuration in Fig. 6 having additionally provided power supply lines connected to the key switch 40. In Fig. 8, the members denoted by the same reference characters as those in Fig. 6 achieve the same operation, and therefore will not be described.

As shown in Fig. 8, the key switch 40 is connected with a backup power supply line 251 and an ACC power supply line 252, a power supply line 253, and a power supply line 254. The backup power supply line 251, the ACC power supply line 252, and the power supply line 253 indicate voltage values when the engine key is at the LOCK position, the ACC position, the IG position, respectively. The power supply line 254 indicates a voltage value when the engine is started.

Figs. 9A to 9D are timing charts for use in illustration of the timing of detecting the start of the engine by the engine start detecting device 30. Figs. 9A,

9B, 9C and 9D represent the voltage waveforms on the backup power supply line 251, the ACC power supply line 252, the IG power supply line 253 and the ST power supply line 254, respectively. A threshold value SL is a prescribed voltage value, 9V for example according to the embodiment. This is set so that the voltage value at the momentary shutoff in a vehicle is lower than the value SL.

The driver inserts the engine key to the LOCK position to release the lock, then turns the engine key to the ACC position (I). This causes the ACC power supply to be on and raised to for example 12V. Then, when the engine key is turned to the ON position (II), the IG power supply is raised and a power supply voltage is supplied for example to the power window or the like. Then, when the engine key is turned to the ST position (III), the starter-motor starts and the voltages on the backup power supply line 251 and the ACC power supply line 252 both fall, and the ST power supply is raised. After a prescribed time period, the engine starts (IV), and the ACC power supply line 252 and the backup power supply line 251 are raised to the original voltage values, and the ST power supply falls, and a steady state is regained. Note that the time period between the ACC position, the starter-motor start and the start of the engine is random. Here, in order to surely avoid the emergency unloading, the start of the engine (the position of IV) needs only be detected and then an activation instruction may be applied to the HDD.

Therefore, the engine start detecting circuit 303 monitors whether or not the value on the ACC power supply line 252 or the IG line 253 exceeds the prescribed threshold value SL through the voltage value monitoring circuit 301. A value beyond the threshold value SL indicates that the engine key is at the ACC or IG position, and therefore it is then monitored whether or not the engine is provided with a power supply. More specifically, the engine start detecting circuit 303 monitors the voltage value on the backup power supply line 251 through the voltage value monitoring circuit 301 and determines if the voltage value on the back up power supply line 251 is lower than the prescribed threshold value SL. Here, it would be possible to monitor whether the two power supply lines, i.e., the backup power supply line 251 and the ACC power supply line 252 are both lower than the prescribed threshold value SL, while monitoring only the ACC power supply line 252 does not allow the engine start to be surely detected. This is because the engine key could be returned from the ACC position to the key LOCK position. Therefore, after the value on the backup power supply line 251 exceeds the prescribed threshold value SL, the backup power supply line 251 or the two power supply lines, i.e., the backup power supply line 251 and the ACC power supply line 252 must be monitored.

Whether or not a power supply is provided for starting the engine may be determined based on the voltage value on

the ST power supply line 254. More specifically, the ST power supply line 254 rises only when a power supply is provided for starting the engine, and therefore the voltage value can be monitored for the purpose.

When the value on the backup power supply line 251 or the values on the backup power supply line 251 and the ACC power supply line 252 are lower than the prescribed threshold value SL, the engine key has come to the ST position (III) through the ACC position (I) and the ON position (II). Then, it is monitored if the engine starts.

More specifically, the engine start detecting circuit 303 monitors the voltage value on the backup power supply line 251 through the voltage value monitoring circuit 301, and determines whether or not the voltage value on the backup power supply line 251 exceeds the prescribed threshold value SL. If the voltage value exceeds the threshold value SL, the engine has started, and therefore an engine start instruction signal is provided to the HDD 15. The engine start may be detected by monitoring whether the values on the two power supply lines, i.e., the backup power supply line 251 and the ACC power supply line 252 exceed the prescribed threshold value SL. Alternatively, it can be monitored whether the value on the ST power supply line 254 is lower than the prescribed threshold value SL.

The HDD 15 receives the instruction signal at the internal CPU 152 and then the magnetic head is allowed to move in response to an instruction from the internal CPU

152.

As described above, according to the embodiment, the voltage values at the four power supply lines, i.e., the backup power supply line 251, the ACC power supply line 252, the IG power supply line 253, and the ST power supply line 254 are monitored to surely detect the start of the engine, and then the magnetic head 51 of the HDD 15 is allowed to move.

Therefore, emergency unloading by a momentary shutoff caused at the start of the engine can be avoided, and the collision between the magnetic head 51 and the ramp 55 at the start of the engine can be prevented. Note that in the above embodiment, a control method to allow the magnetic head 51 to move after the engine start, while the HDD can be kept off before the engine start and then turned on after the start of the engine is detected by the above described part.

The foregoing description is related to the detection of the engine start by monitoring any of voltage values at the four power supply lines 251 to 254 using the engine start detecting device 30. Meanwhile, as shown in Fig. 10, the engine start can be detected based on any of the outputs of the following sensors 304A to 304C.

Detection based on the output of the tachometer 304A

The engine start detecting device 30 monitors the engine revolution through the engine start detecting circuit (microcomputer) 303 and obtains information from

the tachometer through an A/D converting circuit which is not shown. Then, the engine start detecting device 30 determines that the engine has started if the continuous engine revolution has been detected for a certain period.

Sensing using an engine sound detector 304B

Engine sounds are detected inside and outside the vehicle using an engine sound detector 304B, the detected sound is subjected to frequency conversion at the engine start detecting circuit (microcomputer) 303, and the engine start is determined if a frequency spectrum representing the engine revolution is detected for a prescribed time period or longer.

Sensing based on vibration information

Vibration information is sensed using a vibration sensor 304C. The engine start detecting circuit (microcomputer) 303 determines that the engine has started if the difference in the vibration information between the engine inactive state and the engine active state is detected for a prescribed time period or longer.

Detecting based on the output of the generator

The engine start detecting circuit (microcomputer) 303 obtains information about whether or not the generator operates, and determines the engine start based on the operation for a prescribed time period or longer. The engine start detecting circuit (microcomputer) 303 corresponding to a hybrid car obtains information about starter-motor activation and detects the engine start.

0983538-042301

Note that the foregoing description is related to the detection of the engine start using the various sensor outputs followed by the activation of the HDD. Meanwhile, the HDD may be activated in a timing after the vehicle starts moving. In this case, the sensor 16 provided as part of a car navigation system for example may be used to detect the traveling of the vehicle. According to one method, a vehicle speed pulse may be detected. The generation state of the vehicle speed pulse and the timing of activating the HDD are represented in the timing chart in Fig. 11.

In Fig. 11, once the engine key has been inserted followed by the process from (I) to (IV), the engine starts and the vehicle starts moving (V), and an output signal P for the vehicle speed pulse is generated. The pulse signal may be detected by a traveling detection circuit which is not shown and the traveling of the vehicle is detected. Based on the detection signal, the HDD is activated.

Another method of detecting the traveling state of the vehicle is based on the output of a gyro sensor, the OFF output of a parking brake and the like.

As described above, according to the embodiment, based on the output signals of the various sensors which can be used for detecting the traveling state, the traveling of the vehicle is surely detected, and then the magnetic head 51 of the HDD 15 is allowed to move.

As a result, emergency unloading by a momentary

shutoff caused at the start of the engine can be avoided, and the collision between the magnetic head 51 and the ramp 55 at the start of the engine can be prevented. Note that in the embodiment, the magnetic head 51 is allowed to move after the vehicle starts moving, while the HDD may be kept off before the vehicle starts moving and turned on after the vehicle starts moving by the above described part.

As in the foregoing, according to the embodiment, the HDD is activated after the vehicle engine starts or after the vehicle starts moving, and therefore emergency unloading at the start of the engine can surely be avoided.

However, since map data is not displayed on the monitor screen until the HDD is activated, the user might feel insecure. Therefore, in the navigation system according to the embodiment, during the period between the ACC and ON states to the start of the engine, a map stored in the backup RAM 27 and indicating the position of the vehicle the last time the engine has stopped is preferably displayed. Besides the navigation system, in an HDD integrated music information reproducing apparatus for vehicle, information (such as index information) to specify music information performed at the previous engine interruption which has been stored in the backup RAM 27 is preferably displayed.

As described above, according to the present invention, in the HDD for vehicle, the HDD is activated or the head is driven after the engine start is detected or after the

vehicle starts traveling. Therefore, emergency unloading can be prevented at the start of the engine. The reduction in emergency unloading occurrence can reduce the number of collisions between the head and the ramp, so that a disk drive device for vehicle having a head with a prolonged life and improved reliability as an HDD may be provided.

According to the first aspect of the present invention, a disk drive device is driven after the start of the engine in the vehicle is detected by the engine start detecting part, and therefore emergency unloading at the start of the engine can be avoided. As a result, the reduction in emergency unloading occurrence can reduce the number of collisions between the head and the ramp, so that the head has a prolonged life and the disk drive device may have improved reliability as an HDD.

According to the second aspect of the present invention, after an engine start in a vehicle is detected by the engine start detecting part, the movement of the head by the head driving part is allowed. Therefore, the HDD becomes accessible after the engine is activated, so that emergency unloading at the start of the engine can be prevented, and the reduction in emergency unloading occurrence reduces the number of collisions between the head and the ramp. As a result, the head may have a prolonged life and the disk drive device may have improved reliability as an HDD.

According to the third and fourth aspects of the

invention, the head can surely be returned to the retreat position if the power supply is interrupted, and therefore the HDD including the head can be prevented from being critically damaged.

According to the fifth and sixth aspects of the present invention, the engine start can be detected by monitoring the voltages, and the HDD is activated or the head is allowed to move after the detection. Therefore, emergency unloading at the start of the engine can be prevented, and the reduction in emergency unloading occurrence reduces the number of collisions between the head and the ramp. As a result, the head may have a prolonged life and the disk drive device may have improved reliability as an HDD.

According to the seventh to fourteenth aspects of the present invention, the engine start can be detected based on the various sensor outputs or by detecting the traveling of the vehicle. After the detection, the HDD is activated or the head is allowed to move, so that emergency unloading can be prevented at the start of the engine, and the reduction in emergency unloading occurrence reduces the number of collisions between the head and the ramp. As a result, the head may have a prolonged life and the disk drive device may have improved reliability as an HDD.

According to the fifteenth aspect of the present invention, map information in the previous engine off state is backed up in a memory and the map information is

displayed on the screen. Thus, a map is displayed as the driver waits for the HDD to be driven, and therefore the driver may be relieved from vexation during the waiting.

Fig. 12 is a diagram of a disk drive device according to another embodiment of the present invention and shows in detail the configuration of the HDD 15 and the vehicle power supply circuit 25 in Fig. 5 and the engine start detecting device 30 for detecting the start of the engine similarly to Fig. 6.

According to the embodiment, there is a timer LSI 14 which has a time count value set in a programmable manner by a host CPU 11, issues an interrupt at time up, and allows the interrupt routine to take over the processing. Here, the timing of activating the HDD after the start of the engine is specified.

The timing of activating the HDD according to the present invention will be now described in detail. According to the embodiment, at the start of the engine, the HDD is activated after a prescribed time period counted by the timer, so that the number of emergency unloading occurrence is reduced.

Figs. 13A and 13B are timing charts for use in illustration of the timing of activating the HDD using the timer. Fig. 13A shows the voltage waveform on the backup power supply line 251 and Fig. 13B shows the voltage waveform on the ACC power supply line 252. SL (threshold value) represents a prescribed voltage value, 9V for

example according to the embodiment. This voltage is set such that the voltage value at a momentary shutoff in the vehicle is lower than the voltage value SL.

5/23/83
The driver inserts the engine key in the LOCK position to release the lock, and turns the key to the ACC position (I). Thus, the ACC power supply rises for example to 12V, and the key is then turned to the ST position (III) through the ON position (II), which starts the starter-motor and voltage rises both on the backup power supply line 251 and the ACC power supply line 252. After a prescribed time period, the engine starts (IV), and the voltages on the ACC power supply line 252 and the backup power supply line 251 rise again to the original voltage value 12V, and a steady state is regained. Note that the time period between the ACC position, the start of the starter-motor and the start of the engine is random.

The driver inserts the engine key in the LOCK position to release the lock, and turns the key to the ACC position. Thus, the ACC power supply rises. Then, the timer LSI 14 starts counting. The starter-motor starts by the turning of the key to the ST position via the ON position, and the voltages on the backup power supply line 251 and the ACC power supply line 252 both fall. After the rotation of the starter-motor for a prescribed time period, the ACC power supply line 252 and then the backup power supply line 251 rise, and a steady state is regained. The time period between the ACC and ON positions, the start of the starter-

motor and the start of the engine is random.

According to the embodiment, the timer LSI 14 is pre-programmed to count five seconds, and starts counting from the ACC position and after five seconds, an instruction to allow the magnetic head 51 to move is issued to the HDD 15 from the host CPU 11. More specifically, according to the embodiment, the timer is used because a voltage dropped part A may not be lower than the prescribed threshold value SL, and thus the number of emergency unloading occurrence can be minimum.

The HDD 15 receives the instruction signal at the internal CPU 152, and then the magnetic head 51 is allowed to move in response to an instruction from the internal CPU 152.

Note that in the embodiment described above, the magnetic head 51 is allowed to move after the timer has counted a prescribed time period, while the HDD may be kept off before the start of the engine, and turned on when the engine start is detected by the above described part.

Figs. 14A and 14B are timing charts for use in illustration of the timing of activating the HDD using the timer. In Figs. 14A and 14B, the members denoted with the same reference characters as those in Figs. 13A and 13B carry out the same operation, and therefore are not described.

Here, after five seconds, the voltage value on the backup power supply line 251 or the ACC power supply line

252 is monitored and if the value is lower than the threshold value SL, the timer is restarted, and the HDD is activated after three seconds.

Thus, if the engine has not started after the set five seconds, the HDD 15 is activated after another three seconds. Therefore, it may take some time for the engine to start. This operation may be repeated a number of times.

Figs. 15A, 15B, 16A and 16B show embodiments according to which the timer is used and the values of the power supply voltages in the vehicle are monitored and the HDD is activated when prescribed conditions are met.

According to the embodiment shown in Figs. 15A and 15B, the power supply voltages both on the backup power supply line 251 and the ACC power supply line 252 are monitored. The driver inserts the engine key in the LOCK position to release the lock. The ACC power supply rises at the time (timing I) when the key is turned to the ACC position. Then, the voltage value monitoring circuit 301 starts monitoring the voltage values and the timer LSI 14 starts counting.

59
251
Then, when the engine key is turned to the ST position (III) to start the starter-motor, the voltages on the backup power supply line 251 and the ACC power supply line 252 both rise by the voltage dropped state described above.

When the voltage values are lower than the prescribed threshold level SL, the voltage value monitoring circuit 301 can detect its monitoring voltage being lower than the

09030533-042304
T00230-00000000

prescribed threshold level SL. Thus, during the period from (III) to (IV), when the voltage values on the backup power supply line 251 and the ACC power supply line 252 are lower than the prescribed threshold level SL, the time point at which these voltage values once again exceed the threshold level SL is detected, and the start of the engine can be detected. At the time, the HDD can be activated in the engine start timing (IV). Therefore, in this case, the HDD activation by monitoring using the timer is not carried out.

Meanwhile, during the period from (III) to (IV), the voltage values on the backup power supply line 251 and the ACC power supply line 252 may not be lower than the prescribed threshold voltage level SL by a voltage drop (denoted by the chain-dotted line). In this case, the start of the engine cannot be detected by monitoring the power supply voltage values, and therefore the HDD is activated using the timer as shown in Figs. 13A and 13B.

When the engine start is detected or after five seconds counted by the timer, an instruction to allow the magnetic head 51 to move is issued to the HDD 15 from the host CPU 11.

500
23

As described above, according to the embodiment, the timing of activating the HDD varies depending upon the voltage level at a momentary shutoff. If the voltage value at a momentary shutoff is greater than the threshold level (such as the voltage value in Fig. 13A), the HDD is

THE

THE

THE

THE

connection with the embodiment.

As shown in Fig. 17, the key switch 40 is connected with a backup power supply line 251, an ACC power supply line 252, a power supply line 253 and an ST power supply line 254. The backup power supply line 251, the ACC power supply line 252, and the power supply line 253 indicate battery voltage values when the engine key is at the LOCK position, the ACC position, and the IG position, respectively. The ST power supply line 254 indicates a battery voltage value when the engine is started.

Figs. 18A to 18D are timing charts for use in illustration of an embodiment according to which the HDD is activated by both monitoring using the timer and monitoring the voltage values on the power supply lines connected to the key switch. Figs. 18A, 18B, 18C and 18D show voltage waveforms on the backup power supply line 251, the ACC power supply line 252, the IG power supply line 253 and the ST power supply line 254, respectively. SL (threshold value) represents a prescribed voltage value, 9V for example according to the embodiment.

The driver inserts the engine key in the LOCK position to release the lock, and turns the key to the ACC position (I). Thus, the ACC power supply rises for example to 12V. At the time, the timer LSI 14 starts counting.

Then, when the engine key is turned to the ON position (II), the IG power supply rises and a power supply voltage is provided for example to a power window. Note that the

timer LSI 14 may start counting at the time point (II). When the engine key is turned to the ST position (III), the starter-motor starts, the voltages on the backup power supply line 251 and the ACC power supply line 252 both fall because of a momentary shutoff, and the voltage on the ST power supply rises. At the time, the voltage value monitoring circuit 301 detects the momentary shutoff based on the monitoring voltage lower than the threshold level SL. After a prescribed time period, the engine starts (IV), and the voltage values on the backup power supply line 251 and the ACC power supply line 252 rise to the original level and the ST power supply falls, so that a steady state is regained. The voltage value in the steady state can be detected to detect the start of the engine, and therefore at the time point, an instruction to allow the magnetic head 51 to move is issued to the HDD 15 from the host CPU 11.

Meanwhile, during the period from (III) to (IV), the voltage values on the backup power supply line 251 and the ACC power supply line 252 might not be lower than the prescribed threshold level SL by a momentary shutoff (denoted by the chain-dotted line). In this case, the engine starts in a vehicle cannot be detected by monitoring the power supply voltage values, and therefore the HDD is activated using the timer as shown in Figs. 13A and 13B.

When the engine start is detected, or when the timer has counted five seconds, an instruction to allow the

magnetic head 51 to move is issued from the host CPU 11 to the HDD 15.

Whether or not a power supply voltage is provided for starting the engine can be determined based on the voltage value on the ST power supply line 254. More specifically, since the ST power supply line 254 rises only when a power supply voltage is supplied for starting the engine, the voltage value may be monitored for determination. If the voltage value on the ST power supply line 254 is greater than the prescribed threshold level SL, and then becomes lower than the value SL, the engine start can be detected, and therefore the HDD is activated after that. Meanwhile, if the voltage value on the ST power supply line 254 is not higher than the prescribed threshold level SL, the HDD may be activated after five seconds counted by the timer.

Then, when the engine start is detected or after the five seconds counted by the timer, an instruction to allow the magnetic head 51 to move is issued from the host CPU 11 to the HDD 15.

As in the foregoing, according to the embodiment, the voltage values on the four power supply lines, i.e., the backup power supply line 251, the ACC power supply line 252, the IG power supply line 253 and the ST power supply line 254 are monitored to surely detect the start of the engine, and the movement of the magnetic head 51 of the HDD 15 is allowed after the detection. Alternatively, time monitoring is additionally carried out using the timer LSI

14. when conditions of one of the monitoring methods are met, an instruction to allow the magnetic head 51 to move is issued from the host CPU 11 to the HDD 15.

Therefore, emergency unloading caused by a momentary shutoff at the start of the engine can be avoided, and the collision between the magnetic head 51 and the ramp 55 at the start of the engine can be prevented. Note that in the above embodiments, after the engine start, the magnetic head 51 is allowed to move, while the HDD may be kept off before the engine start and may be turned on after the engine start is detected by the above described part.

As in the foregoing, according to the embodiments, the HDD is started after the engine in the vehicle is started, and therefore the emergency unloading at the start of the engine can surely be prevented. However, since in a navigation system, for example, map data is not displayed on the monitor screen before the HDD is activated, the user might feel insecure. Therefore, during the period between the ACC and ON states and the start of the engine, a map stored in the backup RAM and indicating the position of the vehicle the last time the engine is stopped is preferably displayed. Besides the navigation system, in an HDD integrated music information reproducing apparatus, information (such as index information) to specify music information performed at the previous engine interruption which has been stored in the backup RAM 27 is preferably displayed.

As described above, according to the present invention, in a disk drive device driven using a power supply voltage in a vehicle, the start of the engine can be determined by timer monitoring even for a vehicle with no voltage drop at the start of the engine. Meanwhile, for a vehicle with a voltage drop, the disk drive device may be started in an earlier timing. By allowing the head to move after the detection time point, the emergency unloading at the start of the engine can be prevented. Therefore, the number of emergency unloading can be reduced and the number of collisions between the head and the ramp is reduced. As a result, the head may have a prolonged life and the disk drive device may have improved reliability as an HDD.

This application is based on Japanese Patent Application Nos. 2000-123264 and 2000-123265 which are hereby incorporated by reference.

05839538 042301
FILED